

MICRO GOBETIS

2000

P R E P A R A T I O N B O N D I N G C O A T

**READY-MIXED BONDING
COAT FOR SMOOTH OR
LOW POROSITY
SURFACES**

VEGA PLASTER PRIMER

PROPERTIES

MICRO GOBETIS 2000 improves the adhesion for one coat render systems.

Using it will minimise the risk of air pockets occurring in the application of one coat render systems.

CHARACTERISTICS

Appearance: orange-coloured liquid

Nature: dispersion of an acrylic co-polymer

Dry extract: 58 %.

Density: 1.4 ± 0.1 .

Ph: 7 – 7.5.

FIELD OF APPLICATION

Suitable for smooth, low-absorption substrates such as concrete, brick and certain float-smoothed well adhered render surfaces.

MICRO GOBETIS 2000

PREPARATION BONDING COAT



PACKAGING

20 kg bucket.

STOCKAGE

1 year from date of manufacture if stored in unopened original packing in dry, frost-free, cool conditions.

WARRANTEE

- Manufacturer's liability.

TECHNICAL ASSISTANCE

ParexLanko will, on request, provide information and assistance to companies in relation to the use of a specific product.

Such assistance shall not be associated with structural and design conception, nor assume or accept liability for compliance of substrates, nor compliance to instructions provided.

Download the technical data sheet and consult the health and safety document on our new site:

The information provided in this document results from our knowledge of the products and our experience. On-site results may vary, in particular according to the product application methods adopted. Where application methods not covered by this document are used, customers must request specific additional information and/or carry out a representative test before using the products. The above-mentioned information in no way constitutes a warranty relative to the use of the products. Our general terms and conditions of sale shall prevail, in any event, on the information provided in this document. Prior to application, customers and users are requested to check that they have the latest version of this document.